

U.S.S.N. 10/092,335

- 3 -

May 3, 2004

IN THE CLAIMS

Please amend claims 1-15, 21, 22, and 28-31 as indicated below.

1. (Currently Amended) An illuminating waveguide assembly comprising:
a waveguide that includes an elongated solid light transmitting body having:

a first portion extending lengthwise along said body and having a light-transmissive surface, and

a second portion extending lengthwise along said body; and

a vehicle panel having an opening, said waveguide being positioned in said opening with said first portion being exposed at a front side of said panel and said second portion being located behind said panel;

wherein said first portion has a first cross-sectional shape and said second portion has a second, conic cross-sectional shape which directs internally-reflected light towards said first portion such that the light is diffusely transmitted through said opening and out of said body via through said light-transmissive surface, said second cross-sectional shape being different in shape than said first cross-sectional shape.

2. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said first cross-sectional shape is conic, whereby said body has a compound conic cross-sectional shape.

3. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said light transmitting body is made of transparent plastic.

4. (Currently Amended) The illuminating waveguide assembly of claim 3, wherein the light transmitting body is made of acrylic.

5. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said second portion comprises a reflector.

6. (Currently Amended) The illuminating waveguide assembly of claim 5, further comprising a reflective coating on said second portion.

U.S.S.N. 10/092,335

- 4 -

May 3, 2004

7. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said second cross-sectional shape has at least one focal point.
8. (Currently Amended) The illuminating waveguide assembly of claim 7, wherein said second cross-sectional shape is parabolic.
9. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said second cross-sectional shape is faceted.
10. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said first cross-sectional shape is semi-circular.
11. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said first cross-sectional shape is rectilinear.
12. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein the light-transmissive surface of said first portion extends circumferentially around a first side of said body from a first angular location to a second angular location and wherein said second portion has a surface that extends circumferentially around an opposite side of said body from said first angular location to said second angular location.
13. (Currently Amended) The illuminating waveguide assembly of claim 12, further comprising a plurality of mounting flanges extending laterally away from said body at said first and second angular locations, wherein said waveguide is attached to said vehicle panel via said mounting flanges.
14. (Currently Amended) The illuminating waveguide assembly of claim 1, wherein said first and second portions extend from a first end of said elongated body to a second end of said elongated body.
15. (Currently Amended) An illuminating waveguide, comprising:
an elongated solid light transmitting body having:
a first portion extending lengthwise along said body and having a first surface,
and

U.S.S.N. 10/092,335

- 5 -

May 3, 2004

a second portion extending lengthwise along said body and having a second surface;

wherein said first surface is transmissive to light and said second portion has a conic parabolie cross-sectional shape to thereby direct light internally reflecting off said second surface towards said first surface, with the reflected light being diffusely transmitted out of said body through said first surface; and

wherein said first portion and said second portion define the uppermost and lowermost portions of said waveguide, respectively.

16. (Original) The illuminating waveguide of claim 15, wherein said first portion has a conic cross-sectional shape.

17. (Original) The illuminating waveguide of claim 15, wherein said light transmitting body is made of transparent plastic.

18. (Original) The illuminating waveguide of claim 17, wherein said light transmitting body is made of acrylic.

19. (Original) The illuminating waveguide of claim 15, wherein said second portion comprises a reflector.

20. (Original) The illuminating waveguide of claim 19, further comprising a reflective coating on said second portion.

21. (Currently Amended) The illuminating waveguide of claim 15, wherein said conic parabolie cross-section shape of said second portion has at least one focal point.

22. (Currently Amended) The illuminating waveguide of claim 15, wherein said conic parabolie cross-sectional shape of said second portion is faceted.

23. (Original) The illuminating waveguide of claim 15, wherein said first portion has a semi-circular cross-sectional shape.

24. (Original) The illuminating waveguide of claim 15, wherein said first surface of said first portion is rectilinear.

U.S.S.N. 10/092,335

- 6 -

May 3, 2004

25. (Original) The illuminating waveguide of claim 15, wherein said first surface extends circumferentially around a first side of said body from a first angular location to a second angular location and wherein said second surface extends circumferentially around an opposite side of said body from said first angular location to said second angular location.

26. (Original) The illuminating waveguide of claim 25, further comprising a plurality of mounting flanges extending laterally away from said body at said first and second angular locations.

27. (Original) The illuminating waveguide of claim 15, wherein said first and second portions extend from a first end of said elongated body to a second end of said elongated body.

28. (Currently Amended) An illuminating waveguide comprising:
an elongated solid light transmitting body having:

a first portion extending lengthwise along said body and having a light-transmissive surface, and

a second portion extending lengthwise along said body; and

~~one or more~~ mounting features located proximate the intersection of said first and second portions of said light transmitting body, at least two of said mounting feature(s) features being spaced from each other and extending laterally away from said body; and a reflective coating on said second portion extending circumferentially from one of said mounting features to another of said mounting features;

wherein said first portion has a first cross-sectional shape and said second portion has a second cross-sectional shape which directs internally-reflected light towards said first portion for transmission out of said body through said light-transmissive surface, said second cross-sectional shape being different in shape than said first cross-sectional shape.

29. (Currently Amended) The illuminating waveguide of claim 28, wherein said ~~one or more~~ mounting features are elongated flanges that are integrally formed with said body, said flanges extending lengthwise along at least a portion of said body.

30. (Currently Amended) An illuminating waveguide comprising:

U.S.S.N. 10/092,335

- 7 -

May 3, 2004

an elongated solid light transmitting body having:

a first portion extending lengthwise along said body and having a light-transmissive surface, and

a second portion extending lengthwise along said body; and

a plurality of mounting features each extending laterally away from said body from a distal end to a free end;

wherein said free ends of at least two of said mounting features are spaced from each other with said body being located within the space between said free ends; and

one or more mounting features formed as a unitary portion of said body;

wherein said first portion has a first cross-sectional shape and said second portion has a second cross-sectional shape which directs internally-reflected light towards said first portion for transmission out of said body through said light-transmissive surface, said second cross-sectional shape being different in shape than said first cross-sectional shape.

31. (Currently Amended) The illuminating waveguide of claim 30, wherein said ~~one or more~~ mounting feature(s) are elongated flanges that are located proximate the intersection of said first and second portions of said body, said flanges extending lengthwise along at least a portion of said body.